

SECTION 1. Identification of the substance/mixture and of the company/enterprise

1.1. Product identifier

Product name : ADDING OX
Product code: refer to sales department

1.2. Relevant identified uses of the substance or mixture and uses advised against

Additive for alkaline detergents

Sectors of use:

Industrial Manufacturing[SU3], Manufacture of food products[SU4]

Product category:

Washing and Cleaning Products (including solvent based products)

Process categories:

Use in closed process, no likelihood of exposure[PROC1], Use in closed, continuous process with occasional controlled exposure[PROC2], Transfer of substance or mixture (charging and discharging) at dedicated facilities[PROC8B]

Not recommended uses

Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

AEB SpA - Via Vittorio Arici 104 S.Polo - 25134 Brescia (BS) Italy
Tel. +39.030.2307.1 Fax +39.030.2307281
E-mail: info@aeb-group.com - Internet: www.aeb-group.com
E-mail tecnico competente/technical dept.: sds@aeb-group.com

AEB USA
111 N Cluff Avenue
Lodi CA 95240 (USA)
Tel: +1 2096258139 Fax: +1 2092248953
Email: info@aebusa.com - Internet: www.aeb-group.com

AEB AFRICA (PTY) LTD
18 Track Crescent, Cor. Station Road
Montague Gardens 7441
Cape Town (South Africa)
Tel.: +27 215512700 - Fax: +27 (0) 215511919
Email: info@aeb.co.za - Internet: www.aeb-group.com

AEB OCEANIA PTY LTD
178A Wakaden Street
Griffith NSW 2680
T: 1300 704 971
Email: aeboceania@aeb-group.com - Internet: www.aeb-group.com

Produced by
AEB SpA
Via Vittorio Arici 104 S. Polo
25134 Brescia

1.4. Emergency telephone number

AEB SpA

Centralino/Switchboard: +39.030.2307.1 - (h 8.30-12.00 13.30-18.00 GMT +1; Lingua/Language: Italiano, English)

AEB USA

Switchboard: +1 2096258139 (GMT -8; Language: English)

AEB AFRICA (PTY) LTD

Switchboard: +27 215512700 (GMT +1; Language: English, Afrikaans)

AEB OCEANIA PTY LTD

Switchboard: +61 1300 704 971 (GMT +9; Language: English)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:

GHS05, GHS07

Hazard Class and Category Code(s):

Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3

Hazard statement Code(s):

H302 - Harmful if swallowed.

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

Harmful product: do not ingest

If inhaled, the product causes irritation to the respiratory tract, if brought into contact with skin, it causes significant inflammation with erythema, scabs, or edema.

If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):

GHS05, GHS07 - Danger



Hazard statement Code(s):

H302 - Harmful if swallowed.

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

Supplemental Hazard statement Code(s):

not applicable

Precautionary statements:

Prevention

P280 - Wear protective gloves and eye/face protection

Response

P301+P312 - IF SWALLOWED: Call a POISON CENTER or a doctor if you feel unwell

P302+P352 - IF ON SKIN: Wash with plenty of water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or a doctor.

Contains:

Hydrogen peroxide

Contains (Reg.EC 648/2004):

> 30% oxygen-based bleaching agents

2.3. Other hazards

The substance / mixture does NOT contain substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

The use of this chemical agent involves the obligation of "risk assessment" by the employer in accordance with the provisions of Dlgs n. 81. April 9, 2008. Workers exposed to this chemical agent should not be subject to health surveillance if the results of the risk assessment show that, depending on the type and quantity of dangerous chemical agent and method and frequency of exposure to the agent, there is only a "moderate Risk" for the health and safety of workers and that the measures laid down in the Decree are sufficient to reduce the risk.

Do not ingest. Keep out of reach of children.

For professional use only

SECTION 3. Composition/information on ingredients

3.1 Substances

Irrilevant

3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
Hydrogen peroxide	>= 35 < 50%	Ox. Liq. 1, H271; Acute Tox. 4, H302; Skin Corr. 1A, H314; Acute Tox. 4, H332; STOT SE 3, H335; Aquatic Chronic 3, H412	008-003-00-9	7722-84-1	231-765-0	01-2119485 845-22-XXX X

4.1. Description of first aid measures

Inhalation:

Ventilate the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated room. CALL A PHYSICIAN.

If breathing has stopped, give artificial respiration.

Direct contact with skin (of the pure product):

Take off immediately contaminated clothing.

Wash immediately with plenty of running water and possibly with soap, the areas of the body that have, or are only suspected to have, come in contact with the product.

In case of contact with skin, wash immediately with water.

Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately

Do not use eye drops or ointments of any kind before the examination or advice from an oculist.

Ingestion:

The product is harmful and can cause irreversible damages even following a single exposure if swallowed.

Absolutely do not induce vomiting or emesis. Seek medical advice immediately.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation of the dust causes irritation of the mucous membranes, coughing and breathing difficulties. Contact with the skin produces redness and pain. Contact with eyes produces severe redness, pain and deep burns. If ingested it can cause irritation in the mouth, throat and esophagus.

4.3. Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: Call a POISON CENTER or a doctor if you feel unwell

If skin irritation occurs: Get medical advice/attention.

SECTION 5. Firefighting measures

5.1. Extinguishing media

Extinguishing powder or CO2. In the case of more serious fires, also use alcohol-resistant foam and water spray.

5.2. Special hazards arising from the substance or mixture

Do not inhale the gases produced by the explosion and combustion. Burning produces heavy smoke.

5.3. Advice for firefighters

use adequate respiratory equipment.

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel:

Move away from the area surrounding the spill or release. Not smoking. Wear personal protective equipment. (section 8)

6.1.2 For emergency responders:

Wear personal protective equipment. If exposed to vapors / dusts / aerosols wear suitable respiratory equipment. Provide adequate ventilation. Consult the protective measures outlined in section 8.

6.2. Environmental precautions

Contain spills with earth or sand.

If the product has entered a watercourse, sewers or has contaminated soil or vegetation, notify the authorities.

Dispose of the waste material in compliance with the regulations

6.3. Methods and material for containment and cleaning up

6.3.1 Containment:

Rapidly recover the product, wear a mask and protective clothing (for specifications refer to section 8.2. SDS)

Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert material or suck it.

Prevent it from entering the sewer system.

6.3.2 Cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid contact and inhalation of vapors

Wear protective gloves and eye/face protection

At work do not eat or drink.

Do not eat, drink or smoke when using this product.

See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabelled containers.

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Store in a cool and dry place, away from heat sources and direct exposure to sunlight.

7.3. Specific end use(s)

Industrial Manufacturing:

Handle with care Keep in a well ventilated place and away from heat sources (7-30 ° C)

Manufacture of food products:

Handle with care Keep in a well ventilated place and away from heat sources (7-30 ° C)

See the annex exposure scenario.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

=====

Related to contained substances:

Hydrogen peroxide:

Limit value – Eight hours

(ppm)/(mg/m³)

Australia: 1/1,4

Austria: 1/1,4

Belgium: 1/1,4

Canada – Ontario: 1/x

Canada – Québec: 1/1,4

Finland: 1/1,4

France: 1/1,5

Germany (DFG): 0,5/0,71

Ireland: 1/1,5

People's Republic of China: x/1,5

Singapore: 1/1,4

South Korea: 1/1,5

Spain:1/1,4

Sweden: 1/1,4

Switzerland: 0,5/0,71

USA – NIOSH: 1/1,4

USA – OSHA: 1/1,4

United Kingdom: 1/1,4

Limit value – Short term

(ppm)/(mg/m³)

Australia: x/x

Austria: 2/2,8

Belgium: x/x

Canada – Ontario: x/x

Canada – Québec: x/x

Denmark: 2/2,8

Finland: 3(1)/4,2(1)

France: x/x

Germany (DFG): 0,5/0,71

Ireland: 2(1)/3(1)

People's Republic of China: x/x

Singapore: x/x

South Korea: x/x

Spain: x/x

Sweden: 2(1)/3(1)

Switzerland: 0,5/0,71

USA – NIOSH: x/x

USA – OSHA: x/x

United Kingdom: 2/2,8

Remarks

Finland: (1) 15 minutes average value
Ireland: (1) 15 minutes reference period
Sweden: (1) Ceiling limit value

- Substance: Hydrogen peroxide
DNEL
Local effects Long term Workers inhalation = 1,4
Local effects Long term Consumers inhalation = 0,21 (mg/m³)
Local effects Short term Workers inhalation = 3 (mg/m³)
Local effects Short term Consumers inhalation = 1,93 (mg/m³)
PNEC
Sweet water = 0,0126 (mg/l)
sediment Sweet water = 0,047 (mg/kg/sediment)
Sea water = 0,0126 (mg/l)
sediment Sea water = 0,047 (mg/kg/sediment)
intermittent emissions = 0,0138 (mg/l)
STP = 4,66 (mg/l)
ground = 0,0023 (mg/kg ground)

8.2. Exposure controls

Appropriate engineering controls:

Industrial Manufacturing:

No specific monitoring foreseen (act according to good practice and specific rules for the type of risk associated)

Manufacture of food products:

No specific monitoring foreseen (act according to good practice and specific rules for the type of risk associated)

8.2.2 Individual protection measures:

(a) Eye / face protection

Wear protective goggles (EN 166).

(b) Skin protection

(i) Hand protection

Durante la manipolazione del prodotto puro usare guanti protettivi resistenti ai prodotti chimici (EN 374-1/EN374-2/EN374-3)

Nitrile rubber, breakthrough time:> = 480 min, Glove thickness: 0.7 mm

Natural rubber, breakthrough time:> = 480 min, Glove thickness: 1 mm

Butyl rubber, breakthrough time:> = 480 min, Glove thickness: 0.33 mm

(ii) Other

When handling the pure product, wear full protective clothing (generic workwear / antacid, safety shoes S3-EN ISO 20345) or other protective equipment, according to the instructions of the employer

(c) Respiratory protection

Not needed for normal use.

During manual operations in case of insufficient ventilation and / or by provisions by the employer and / or by

evaluations of environmental hygiene investigations, use mask with filters for Universal type ABECK (UNI EN 405)

(d) Thermal hazards

No hazard to report

Environmental exposure controls:

Use according to good working practices and avoid to disperse the product into the environment.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Appearance	clear colorless liquid	
Odour	not determined as considered not relevant for the characterization of the product	
Odour threshold	not determined as considered not relevant for the characterization of the product	
pH	<2.0 ± 0.5 (20 ° C); 7.0 ± 0.5 (20 ° C, sol% 0.5)	
Melting point/freezing point	not determined as considered not relevant for the characterization of the product	
Initial boiling point and boiling range	not determined as considered not relevant for the characterization of the product	
Flash point	not determined as considered not relevant for the characterization of the product	ASTM D92
Evaporation rate	not determined as considered not relevant for the characterization of the product	
Flammability (solid, gas)	not determined as considered not relevant for the characterization of the product	
Upper/lower flammability or explosive limits	not determined as considered not relevant for the characterization of the product	
Vapour pressure	not determined as considered not relevant for the characterization of the product	
Vapour density	not determined as considered not relevant for the characterization of the product	
Relative density	1.20 ± 0.05 g / ml (20 ° C)	
Solubility	in water	
Water solubility	miscible	
Partition coefficient: n-octanol/water	not determined as considered not relevant for the characterization of the product	
Auto-ignition temperature	not determined as considered not relevant for the characterization of the product	
Decomposition temperature	not determined as considered not relevant for the characterization of the product	
Viscosity	not determined as considered not relevant for the characterization of the product	
Explosive properties	not determined as considered not relevant for the characterization of the product	
Oxidising properties	not determined as considered not relevant for the characterization of the product	

9.2. Other information

No data available.

SECTION 10. Stability and reactivity

10.1. Reactivity

It is not pyrophoric.

10.2. Chemical stability

Stable under recommended storage and handling conditions.

10.3. Possibility of hazardous reactions

Possible dangerous reaction with reducing agents, alkalis, combustible materials, heavy metal compounds

10.4. Conditions to avoid

Keep away from heat sources.

10.5. Incompatible materials

reducing agents, alkalis, combustible materials, heavy metal compounds

10.6. Hazardous decomposition products

Oggigeno

SECTION 11. Toxicological information

11.1. Information on toxicological effects

ATE(mix) oral = 1.272,4 mg/kg

ATE(mix) dermal = ∞

ATE(mix) inhal = 32,3 mg/l/4 h

(a) acute toxicity: Harmful product: do not ingest

Hydrogen peroxide: Ingestion-rat LD50 (mg/kg/bw 24h): 635-1020

Skin contact-LC50 rat/coniglio (mg/kg/bw 24h): > 2000

Inhalation-rat LD50 (mg/l/4h): > 16.1

(b) skin corrosion/irritation: If brought into contact with the skin, the product causes significant inflammation with erythema, scabs, or edema.

Hydrogen peroxide: Corrosive

Hydrogen peroxide: Irritation

(c) serious eye damage/irritation: If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

Hydrogen peroxide: Corrosive

Hydrogen peroxide: Irritation

(d) respiratory or skin sensitization: Hydrogen peroxide: Non-sensitizing

(e) germ cell mutagenicity: Hydrogen peroxide: Non-mutagenic

(f) carcinogenicity: Hydrogen peroxide: Non-carcinogenic

(g) reproductive toxicity: Hydrogen peroxide: Non-toxic for reproduction

(h) specific target organ toxicity (STOT) single exposure: If inhaled, the product causes irritations to the respiratory tract.

Hydrogen peroxide: toxic exposure to the respiratory tract with route of exposure inhalation

(i) specific target organ toxicity (STOT) repeated exposure: Hydrogen peroxide: Not available

(j) aspiration hazard: Hydrogen peroxide: Not available

SECTION 12. Ecological information

12.1. Toxicity

=====

Related to contained substances:

Hydrogen peroxide:

Acute toxicity-fish LC50 (mg/l/83d): 13.1 -20.5

Acute toxicity-crustacea EC50 (mg/l/48 h): 2.4

Acute algae toxicity ErC50 (mg/l/72-69): 1.38

Use according to good working practices and avoid to disperse the product into the environment.

12.2. Persistence and degradability

=====

Related to contained substances:

Hydrogen peroxide:

Readily biodegradable

12.3. Bioaccumulative potential

=====

Related to contained substances:

Hydrogen peroxide:

Not available

12.4. Mobility in soil

=====

Related to contained substances:

Hydrogen peroxide:

Henry's Law constant (H): Pa * 0.0075 m3/mol

12.5. Results of PBT and vPvB assessment

No PBT/vPvB ingredient is present

12.6. Other adverse effects

No adverse effects

Regulation (EC) No 2006/907 - 2004/648

The (l) surfactant (s) content (s) in this preparation complies (comply) with (i) the biodegradability criteria as laid down in Regulation CE/648/2004 on detergents. All data are held at the disposal of the competent authorities of Member States and will be provided, at their direct request or at the request of a detergent manufacturer, to those authorities.

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies.

Recover if possible. Operate according to local or national regulations

SECTION 14. Transport information

14.1. UN number

ADR/RID/IMDG/ICAO-IATA: 2014

If subject to the following characteristics is ADR exempt:

Combination packagings: per inner packaging 1 L per package 30 Kg

Inner packaging placed in shrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 Kg



14.2. UN proper shipping name

ADR/RID/IMDG: PEROSSIDO DI IDROGENO IN SOLUZIONE ACQUOSA contenente almeno il 20% ma al massimo il 60% di perossido di idrogeno (stabilizzata se necessario)

ADR/RID/IMDG: HYDROGEN PEROXIDE, AQUEOUS SOLUTION with not less than 20% but not more than 60% hydrogen peroxide (stabilized as necessary)

ICAO-IATA: HYDROGEN PEROXIDE, AQUEOUS SOLUTION with not less than 20% but not more than 60% hydrogen peroxide (stabilized as necessary)

14.3. Transport hazard class(es)

ADR/RID/IMDG/ICAO-IATA: Class : 5.1

ADR/RID/IMDG/ICAO-IATA: Label : 5.1+8

ADR: Tunnel restriction code : E

ADR/RID/IMDG/ICAO-IATA: Limited quantities : 1 L

IMDG - EmS : F-H, S-Q

14.4. Packing group

ADR/RID/IMDG/ICAO-IATA: II

14.5. Environmental hazards

ADR/RID/ICAO-IATA: Product is not environmentally hazardous
IMDG: Marine polluting agent : No

14.6. Special precautions for user

The transport must be carried out by authorized vehicles for the transport of dangerous goods in accordance with the requirements of the applicable Edition of the agreement A.D.R. and national provisions. The transport must be carried out in the original packaging and in packages that are made from materials resistant to content and not likely to generate with this dangerous reactions. The process of loading and unloading of dangerous goods have received adequate training on the risks presented by prepared and on possible procedures to be taken in the event of emergency situations

14.7. Transport in bulk according to Annex II of MARPOL73/78 and IBC Code

Transport in bulk is not foreseen

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions relating to the product or contained substances (All. XVII Reg. EC 1907/2006): not applicable
Substances in Candidate List (art. 59 Reg. EC 1907/2006): the product does not contain SVHC
Substances subject to authorisation (Ann. XIV Reg. CEC 1907/2006): the product does not contain SVHC
Reg. EC 648/04: see 2.2
Reg. (EU) n. 1169/2011: see 2.2
Reg (UE) 528/2012: see.to 2.2

REGULATION (EU) No 1357/2014 - waste:
HP4 - Irritant — skin irritation and eye damage
HP5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

15.2. Chemical safety assessment

No chemical safety assessment was carried out by the supplier

SECTION 16. Other information

16.1. Other information

Points modified from the previous revision: 1.2, 7.3, 8.1, 8.2, 10, 11,

Description of hazard statements set out in paragraph 3

H271 = May cause fire or explosion; strong oxidiser.
H302 = Harmful if swallowed.
H314 = Causes severe skin burns and eye damage.
H332 = Harmful if inhaled.
H335 = May cause respiratory irritation.
H412 = Harmful to aquatic life with long lasting effects.

Classification based on data of all mixture components

Main normative references:

Reg. (CE) n. 1907 del 18/12/06 REACH (Registration, Evaluation and Authorisation of CHemicals) et seq.
Reg. (CE) 1272/2008 CLP (Classification Labelling and Packaging) et seq.
Regulation (EC) n. 648 of 31/03/04 (on detergents) et seq.
Regulation (UE) n. 1169/2011 (on the provision of food information to consumers)
Directive 2012/18/EU (on the control of major-accident hazards involving dangerous substances) et seq.
Regulation (UE) 528/2012 (Biocides) et seq.

Procedure used to classify under CLP mixture (Reg . EC 1272/2008): similar mixture

Training required: This document must be submitted to the employer to determine the possible need for appropriate training for workers to ensure protection of human health and the environment.

n.a.: not applicable

n.d.: not available

ADR: Accord européen relative au transport International des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ATE: Acute Toxicity Estimat

BFC: BioconCentration Factor

BOD: Biochemical Oxigen Demand

CAS: Chemical Abstract Service number

CAP: Centre AntiPoison

CE/EC number EINECS (European Inventory of existing Commercial Substances) e ELINCS (European List of notified Chemical Substances)

CL50/LC50: Lethal Concentration 50

DL50/LD50: Lethal Dose 50

COD: Chemical Oxygen Demand

DNEL: Derived No Effect Level

EC50: half maximal Effective Concentration

ERC: Enviroment Release Classes

EU/UE: European Union

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

IMDG: International Maritime Dangerous Goods code

Kow: Octanol water partition coefficient

NOEC: No Observed Effect Concentration

OEL: Occupational Exposure Limit

PBT: Persistent Bioaccumulative and Toxic

PC: Product Categories

PNEC: Predicted No Effect Concentration

PROC: Process Categories

RID: Règlement concernent le transport International ferroviaire des marchandises dangereuses (Regulations concerning International rail transport of dangerous goods)

STOT: Target Organ Systemic Toxicity

STOT (RE): Repeated Exposure

STOT (SE): Single Exposure
STP: Sewage Treatment Plants
SU: Sector of Use
SVCH: Substance of Very High Concern
TLV: Threshold Limit Value
vPvB: Very Persistent Very Bioaccumulative

References and Sources:

- ECHA Registered Substances:
- <https://echa.europa.eu/web/guest/information-on-chemicals/registered-substances>
- SDS supplier
- GESTIS DNEL Database: <http://www.dguv.de/ifa/gestis/gestis-dnel-datenbank/index-2.jsp>
- GESTIS International Limit Value: <http://limitvalue.ifa.dguv.de>

This msds was made in good faith by AEB technical Office on the basis of the information available at the date of the last revision. The person in charge must regularly inform the employees about the specific risks they encounter when using this substance/product. The information contained here relate only to the substance/the preparation indicated and may not apply if the product is used improperly or in combination with others. Nothing contained herein shall be construed as a guarantee, either express or implied. It is the responsibility of the user to ensure the opportunities and completeness of the information contained herein for their own particular use.

*** this tab annuls and replaces any previous edition. (IIXX)

Changes to the previous edition: section 1,8,10,11,12 - Exposure scenarios - Work instruction sheet update

SUMI**Safe Use of Mixtures Information****AISE_SUMI_IS_4_1***Version 1.1, August 2018****Industrial uses; Automated task; Semi-automated task; Dedicated equipment***

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

The SUMI applies to industrial uses where products are used in closed process where opportunity for exposure arises. This Safe Use Information is based on the **AISE_SWED_IS_4_1**.

Operational Conditions

Maximum duration	480 minutes per day.
Range of application / Process conditions	Indoor Use. Process carried out at room temperature. In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per hour). No LEV required.

Risk Management Measures

Measures related to personal protective equipment (PPE), hygiene and health evaluation	See section 8 of the SDS of this product for specifications.
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental measures	Prevent that undiluted product reaches surface waters.
	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use resulting in release to municipal sewage treatment plant.

Additional good practice advice

<p>Don't eat or drink. Don't smoke. Don't use in proximity of open flame.</p>	
<p>Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.</p>	
<p>Spillage instructions</p>	<p>Dilute with fresh water and mop up.</p>
<p>Hygiene practices</p>	<p>Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.</p>

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

SUMI**Safe Use of Mixtures Information****AISE_SUMI_IS_8b_1***Version 1.1, August 2018****Transfer and dilution of concentrated product by using dedicated dosing system***

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.


General description of the process covered

This SUMI applies to industrial uses where products are transferred to or diluted in a dedicated dosing system. This Safe Use Information is based on the **AISE_SWED_IS_8b_1_L** and **AISE_SWED_IS_8b_1_S**


Operational Conditions

Maximum duration	60 minutes per day.
Range of application / Process conditions	Indoor Use.
	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per hour). No LEV required.

Risk Management Measures

Measures related to personal protective equipment (PPE), hygiene and health evaluation	Wear suitable gloves. See section 8 of the SDS of this product for specifications.
	 Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental measures	Prevent that undiluted product reaches surface waters.
	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use resulting in release to municipal sewage treatment plant.

Additional good practice advice

<p>Don't eat or drink. Don't smoke. Don't use in proximity of open flame.</p>	
<p>Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.</p>	
<p>Spillage instructions</p>	<p>Dilute with fresh water and mop up.</p>
<p>Hygiene practices</p>	<p>Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.</p>

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

SUMI**Safe Use of Mixtures Information****AISE_SUMI_IS_13_4***Version 1.1, August 2018****Industrial uses; Treatment of articles by dipping or pouring***

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

This SUMI applies to industrial uses where articles are treated by dipping or pouring. This Safe Use Information is based on the **AISE_SWED_IS_13_4**.

Operational Conditions

Maximum duration	480 minutes per day.
Range of application / Process conditions	Indoor Use. Process carried out at room temperature. In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per hour). No LEV required.

Risk Management Measures

Measures related to personal protective equipment (PPE), hygiene and health evaluation	See section 8 of the SDS of this product for specifications.
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental measures	Prevent that undiluted product reaches surface waters.
	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use resulting in release to municipal sewage treatment plant.

Additional good practice advice

<p>Don't eat or drink. Don't smoke. Don't use in proximity of open flame.</p>	
<p>Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.</p>	
<p>Spillage instructions</p>	<p>Dilute with fresh water and mop up.</p>
<p>Hygiene practices</p>	<p>Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.</p>

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

WORKING ISTRUCTION TABLE



This tab provides instructions for appropriate and safe use of products and proper management of emergency situations for cleaning staff/users.

Attached to MSDS rel#9 del 08/20/20

Use description	Use in batch and other process (synthesis) where opportunity for exposure arises [PROC4]; Transfer of substance or mixture (charging and discharging) at dedicated facilities [PROC8b]; Treatment of articles by dipping and pouring [PROC13]
Product name	ADDING OX
Classification of the product (100%)	H302 - Harmful if swallowed. H315 - Causes skin irritation. H318 - Causes serious eye damage. H335 - May cause respiratory irritation.
Classification of the diluted product (maximum use concentration)	At maximux concentration of use (0,5%) the product is classified: Non hazardous according to Regulation (EC) No 1272/2008
Handling of the product (100%)	Avoid contact and inhalation of vapors Wear protective gloves and eye/face protection. At work do not eat or drink.
Handling of the diluted product	At work do not eat or drink.
DPI required concentrated product (racking, concentrated use, spillage...)	Chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3).
Diluted product	No DPI required for intended uses

In case of emergency (accidents involving exposure to the product)	Immediately inform the customer. Immediately inform the employer. Contact Poisons Centres tel. number in 1.4 section of the MSDS
Accidental release large quantities measures: concentrated product	Wear gloves, glasses and protective clothing (for specifications refer to section 8.2. SDS) Possibly absorb it with inert materia or sucked it. After wiping up, wash with water the area and materials involved
Diluted product	Wash with water the area and materials involved
Storage of the product	Keep in original container closed tightly. Do not store in open or unlabelled containers. Keep containers upright and safe by avoiding the possibility of falls or collisions. Store in a cool and dry place, away from heat sources and direct exposure to sunlight.
In case of accidents, emergency or fire	Immediately inform the customer. Follow company emergency instruction.